

---

**COMPUTER SCIENCE**

**9608/23**

Paper 2 Written Paper

**May/June 2016**

MARK SCHEME

Maximum Mark: 75

---

**Published**

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2016 series for most Cambridge IGCSE<sup>®</sup>, Cambridge International A and AS Level components and some Cambridge O Level components.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9608	23

1 (a) (i)

[6]

Item	Statement	Selection	Iteration	Assignment
1	WHILE DegF > 37.5		✓	
2	MyName = "Gordon"			✓
3	DegF = INT(DegF)			✓
4	ENDIF	✓		
5	CASE OF MyFavourite	✓		
6	UNTIL x = 5		✓	

One mark per row

Additional ticks in any row cancels that row

(ii)

[6]

Item	Purpose of statement
1	(Start of) loop – repeat while <u>DegF</u> greater than <u>37.5</u>
2	Assign (string) <u>"Gordon"</u> to <u>MyName</u>
3	Assign <u>integer</u> value / whole number part of <u>DegF</u> to <u>DegF</u>
4	End of an IF statement / selection statement
5	Head of CASE / selection statement based on variable <u>MyFavourite</u>
6	End of REPEAT / post-condition <u>loop</u> : repeated until x equals 5

Exact wording not important

Explanation must refer to variables or values used in code (except for row 4)

(iii)

[2]

Expression	Result
'P' & MID(MyString, 13, 4)	"Paint"
RIGHT(MID(MyString, 6, 10), 4)	"Main"

Must have correct case

Quotation marks optional

<b>Page 3</b>	<b>Mark Scheme</b>	<b>Syllabus</b>	<b>Paper</b>
	<b>Cambridge International AS/A Level – May/June 2016</b>	<b>9608</b>	<b>23</b>

2 (a)

[5]

<b>Identifier</b>	<b>Data Type</b>	<b>Description</b>
<b>Accelerator</b>	<b>INTEGER</b>	Accelerator position Values: 0 to 100 in steps of 1  Meaning: 0 : none (not pressed) 100: maximum (fully pressed)
<b>EngineTemp</b>	<b>REAL / FLOAT / SINGLE / DOUBLE</b>	Engine temperature in °C (–50 to +150 correct to 1 decimal place)
<b>NormalTemp</b>	<b>INTEGER</b>	Normal engine temperature in °C Whole number; typical value 90
<b>Speed</b>	<b>INTEGER</b>	Road speed of car (in km/hr) Values: 0 to 200 in steps of 1
<b>EngineStop</b>	<b>BOOLEAN</b>	Value used to signal engine must be stopped  Possible values: TRUE: stop engine FALSE: run engine

One mark per row  
Data types as shown

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9608	23

(b) [6]

```

INPUT Accelerator
INPUT EngineTemp
INPUT NormalTemp
INPUT Speed
    
```

```

    } ①
    } ③
    ② {
    IF Accelerator = 0 AND EngineTemp >= NormalTemp AND Speed = 0
    THEN
        EngineStop ← TRUE ④
    ELSE
        EngineStop ← FALSE ⑤
    ENDIF
    OUTPUT "Engine Stopped" ⑥
    
```

Mark points as circled, descriptions as below:

1. Four INPUT statements (correct names and sequence)
2. Correct IF..THEN..ELSE..ENDIF including first condition (or equivalent nested IFs)
3. Correct second and third conditions
4. Correct THEN statement
5. Correct ELSE statement
6. Output indicating EngineStop  
(Following ENDIF or as **two** separate statements within THEN and ELSE)

3 (a) [11]

```

FUNCTION Decrypt (Lookup : ARRAY, CipherChar : CHAR) RETURNS CHAR
    DECLARE Found : BOOLEAN
    DECLARE Index : INTEGER
    DECLARE OriginalChar : CHAR

    Index ← 1 //start with first element in the array //
                assign the start index

    Found ← FALSE
    //now search for CipherChar in Lookup:
    WHILE Found = FALSE // Found <> TRUE // NOT Found
        // compare CipherChar with this array element:
        IF Lookup[Index] = CipherChar
            THEN
                Found ← TRUE // Set the flag
            ELSE
                Index ← Index + 1 //Move to next array element
        ENDIF
    ENDWHILE
    //dropped out of loop so must have found CipherChar:
    OriginalChar ← CHR(Index) // convert Index to original character
    RETURN OriginalChar

ENDFUNCTION
    
```

One mark for each part-statement (shown underlined and bold)

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9608	23

- (b) 'Pseudocode' solution included here for development and clarification of the mark scheme. Programming language example solutions appear in the Appendix. [6]

```

INPUT StartIndex
INPUT NumberToOutput } ①

FOR Index ← StartIndex to StartIndex + NumberToOutput - 1
    OriginalChar ← CHR(Index) ③
    CipherChar ← Lookup[Index] ④
    OUPUT ("Index " & Index & ": Character " & OriginalChar & ⑤
           " has substitute character " & CipherChar) ⑥
ENDFOR
    
```

② {


Mark points as circled, descriptions as below:

1. Two INPUT statements
2. Working loop using Index (allow alternative solutions including separate loop counter)
3. Assignment (using correct values of Index or other variable)
4. Assignment (using correct values of Index or other variable)
5. One mark for OUTPUT of a string combining text and variables...
6. ...a second mark if OUTPUT string is completely correct

- 4 (a) • Functions / Procedures [2]  
 • Ability to pass parameters between modules  
 • Use of local / global variables

(b) (i)

[1]



One mark for correct arrow as shown – accept either direction

(ii)

[4]

Data Item	Parameter					
	A	B	C	D	E	F
Product ID	✓	✓		✓	(✓)	
Quantity				(✓)	✓	
Flag Value – indicating operation success or fail			✓			✓

Mark as follows:

- Row 1: One mark for tick in A **AND** B, one mark for D **OR** E
- Row 2: One mark for D **OR** E (must be opposite of Row 1)
- Row 3: One mark for C **AND** F

Page 7	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9608	23

5 (a) (i) **Explanation:** [Max 3]

- Easier to separate the two strings // to retrieve / search for / edit (text relating to a CD)
- Obvious where `CDTitle` ends and `CDArtist` begins

**Drawback:**

- Takes up more / unnecessary space in the file
- If the string is bigger than 40 characters then data will be lost // string length is limited
- The additional spaces will need to be removed before strings can be used

One mark per bullet

(ii) **Problem:** File `mode = WRITE` / file is opened for writing // by explanation [3]

**Effect:** All existing file lines / contents / data will be overwritten / deleted / lost

**Solution:** `WRITE` should be changed to `APPEND` (allow meaningful example)

Allow first two mark points to be interchanged – read as one paragraph.

<b>Page 8</b>	<b>Mark Scheme</b>	<b>Syllabus</b>	<b>Paper</b>
	<b>Cambridge International AS/A Level – May/June 2016</b>	<b>9608</b>	<b>23</b>

- (b) 'Pseudocode' solution included here for development and clarification of mark scheme.  
Programming language example solutions appear in the Appendix. **[Max 10]**

```

PROCEDURE OutputLocationList ()

    DECLARE CDTitle : STRING
    DECLARE CDArtist : STRING
    DECLARE CDSearch : STRING
    DECLARE FileData : STRING
    DECLARE Total : INTEGER
    DECLARE FileData : STRING

    Total ← 0

    OPENFILE "MyMusic" FOR READ

    OUTPUT "Input Location"
    INPUT CDSearch

    WHILE NOT EOF("MyMusic")
        READFILE ("MyMusic", FileData
        IF RIGHT(FileData, 8) = CDSearch
        THEN
            CDTitle ← LEFT(FileData, 40)
            CDArtist ← MID(FileData(41, 40)
            OUPUT (CDTitle & " - " & CDArtist)
            Total ← Total + 1
        ENDIF
    ENDWHILE

    OUTPUT (Total & " CDs found")
    CLOSEFILE("MyMusic")

ENDPROCEDURE
  
```

One mark for each of the following:

- Procedure heading and ending
- Declaration AND initialisation of variable used as counter (Total above)
- Prompt and input of location to search for CDSearch (or other name)
- Open file for reading (Allow MyMusic or MyMusic.txt)
- Working conditional loop structure including test for EOF

The following points must be present inside a loop

- Read a line from the file (or read complete file in one e.g. as list)
- Isolate 8 chars representing location **and** compare with CDLocation
- Extract strings representing CDTitle and CDArtist
- Output CDTitle and CDArtist (separator optional) if correct location found
- Increment Total if correct location found

The following points must be present after a loop

- Output message including number of CDs found at location (Total)
- Close file



Page 9	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9608	23

6 (a) (i)

[4]

n	x	Flag	m	NewString
–		TRUE	7	“”
1	‘B’	FALSE		“B”
2	‘i’			“Bi”
3	‘g’			“Big”
4	‘∇’	TRUE		“Big∇”
5	‘B’	FALSE		“Big∇B”
6	‘e’			“Big∇Be”
7	‘n’			“Big∇Ben”

 One mark per correct column (**columns 3 and 4 count as 1**)

- Arrows indicate required sequence (i.e. “B” can’t be in row before TRUE)
- Letter case must be as shown
- Ignore quotation symbol
- Allow “ “ or ∇ for space symbol

(ii) (To return a string where:)

[2]

- The first character of each word is capitalised / made upper case // by explanation
- The remaining characters (of each word) are made lower case

 (b) (i) • The function operates normally // returns an ‘empty string’

[1]

(ii) Examples of suitable test strings:

[3]

- Strings with all capitals
- Strings with all lower case
- Strings with first letters of words already capitalised (i.e. in correct format)
- Strings in “reverse” format – i.e. first letters lower case, the rest upper case
- String with only one word
- Strings with multiple spaces
- Strings with numbers / symbols

 One mark for each string example **plus** supporting explanation.

<b>Page 10</b>	<b>Mark Scheme</b>	<b>Syllabus</b>	<b>Paper</b>
	<b>Cambridge International AS/A Level – May/June 2016</b>	<b>9608</b>	<b>23</b>

### Appendix – Program Code Example Solutions

#### Q3 (b): VB.NET

```
Console.WriteLine("Enter start position")
StartIndex = Console.ReadLine()
Console.WriteLine("Enter how many")
NumberToOutput = Console.ReadLine()
For Index = StartIndex To StartIndex + NumberToOutput - 1
    OriginalChar = Chr(Index)
    CipherChar = Lookup(Index)
    Console.WriteLine("Index " & Index & ": Character " & OriginalChar &
        " has substitute character " & CipherChar)
Next Index
```

#### Q3 (b): Pascal

```
Writeln('Enter start position');
Readln(StartIndex);
Writeln('Enter how many');
Readln(NumberToOutput);
For index := StartIndex To StartIndex + NumberToOutput - 1 Do
Begin
    OriginalChar := chr(index);
    CipherChar := Lookup[index];
    writeln("Index " + index + ": Character " + OriginalChar +
        " has substitute character " & CipherChar);
end;
```

#### Q3 (b): Python

```
startIndex = int(input("enter start position"))
numberToOutput = int(input("enter how many"))
for index in range(startIndex, (startIndex + numberToOutput)) :
    OriginalChar = chr(index)
    CipherChar = Lookup[index]
    print("Index " + (index) + ": Character " + OriginalChar +
        " has subst char " + CipherChar)
```

Page 11	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9608	23

**Q5 (b): VB.NET****A StreamReader() solution:**

```
Sub OutPutLocationList()  
  
    Dim Total As Integer  
    Dim FileData As String  
    Dim ObjReader As IO.StreamReader  
    ObjReader = New IO.StreamReader("C:\MyMusic.txt")  
    Dim CDLocation As String  
    Dim CDTitle As String  
    Dim CDArtist As String  
  
    Total = 0  
    Console.WriteLine("Input location to search ")  
    CDSearch = Console.ReadLine  
    Do While ObjReader.Peek <> -1  
        FileData = ObjReader.ReadLine()  
        If Right(FileData, 8) = CDLocation Then  
            CDTitle = Left(FileData, 40)  
            CDArtist = Mid(FileData, 41, 40)  
            Console.WriteLine(CDTitle & " " & CDArtist)  
            Total = Total + 1  
        End If  
    Loop  
    Console.WriteLine(Total & " CDs were found")  
    ObjReader.Close()  
End Sub
```

**A legacy FileOpen() solution:**

```
Sub OutPutLocationList()  
  
    Dim Total As Integer  
    Dim FileData As String  
    FileOpen (1, "C:\MyMusic.txt", OpenMode.Input)  
    Dim CDLocation As String  
    Dim CDTitle As String  
    Dim CDArtist As String  
  
    Total = 0  
    Console.WriteLine("Input location to search ")  
    CDSearch = Console.ReadLine  
    Do While NOT EOF(1)  
        Input(1, FileData)  
        If Right(FileData, 8) = CDSearch Then  
            CDTitle = Left(FileData, 40)  
            CDArtist = Mid(FileData, 41, 40)  
            Console.WriteLine(CDTitle & " " & CDArtist)  
            Total = Total + 1  
        End If  
    Loop  
    Console.WriteLine(Total & " CDs were found")  
    FileClose(1)  
End Sub
```

Page 12	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2016	9608	23

### Q5 (b): Pascal

```

procedure OutputLocationList;
var
  FileData, CDLocation, CDTitle, CDArtist : String;
  CDFile : Textfile;
  Total : Integer;
Begin
  Total := 0;
  Writeln('Input location to search ');
  Readln(CDSearch);
  AssignFile(CDFile, 'MyMusic.txt');
  Reset(CDFile);

  While not eof(CDFile) Do
  Begin
    readln(CDFile, FileData);
    If copy(FileData, 80, 8) = CDSearch Then
    Begin
      CDTitle := copy(FileData, 1, 40);
      CDArtist := copy(FileData, 41, 40);
      Writeln(CDTitle + ' : ' + CDArtist);
      Total := Total + 1;
    End;
  End;

  Writeln(Total + ' CDs were found')
  CloseFile(CDFile);

End

```

### Q5 (b): Python

```

#total : Integer
#CDSearch, LineOfText, LineString : String

Def OutPutLocationList():
    FileHandle = open("MyMusicPy.TXT", "r")
    total = 0
    CDSearch = input("Enter location to search")
    LineOfText = FileHandle.readline()
    while len(LineOfText) > 0:
        LineString = LineOfText[80:87] #extact last 8 characters
(location)
        if LineString == CDSearch:
            total = total+1
            CDTitle = LineOfText[0:39] #extract CD title
            CDArtist = LineOfText[40:79] #extract CD artist
            print(CDTitle + ": " + CDArtist)
            LineOfText = FileHandle.readline() #read next line
    print("There are " + str(total) + " in that location")
    FileHandle.close()

```