
COMPUTER SCIENCE

9608/32

Paper 3 Written Paper

May/June 2017

MARK SCHEME

Maximum Mark: 75

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2017 series for most Cambridge IGCSE[®], Cambridge International A and AS Level and Cambridge Pre-U components, and some Cambridge O Level components.

© IGCSE is a registered trademark.

This document consists of **7** printed pages.

Question	Answer	Marks
1(a)(i)	DECLARE NewFriend : MyContactDetail	1
1(a)(ii)	NewFriend.HouseNumber ← 129	1
1(b)	<p>Declaration of Name, Area, HouseNumber 1</p> <p>Inclusion of three correct values for Area 1</p> <p>Inclusion of correct range for HouseNumber 1</p> <p>For example:</p> <pre> TYPE MyContactDetail DECLARE Name : STRING DECLARE Area : (uptown, downtown, midtown) DECLARE HouseNumber : 1..499 ENDTYPE </pre> <p style="text-align: right;">1 1 & 1</p>	3
1(c)(i)	4402	1
1(c)(ii)	33	1
1(c)(iii)	3427	1
1(c)(iv)	TRUE	1
1(d)(i)	IPointer ← @MyInt2	1
1(d)(ii)	MyInt1 ← 33	1
1(d)(iii)	IPointer^ ← MyInt2	1

Question	Answer	Marks
2(a)(i)	Pharming	1
2(a)(ii)	Phishing	1
2(a)(iii)	A <u>standalone/independent</u> piece of malicious software that can replicate/duplicate itself	1 1 2
2(b)	No up-to-date anti-virus (or equivalent) software (used) / Regular virus scans not performed No firewall Operating system not up-to-date/obsolete Attachments/suspicious links in emails clicked on Clicking on website with an out of date security certificate	max 2 2
2(c)(i)	(Certificate) serial number Certificate Authority (that issued certificate) Valid date(s) // Date of expiry Subject name (name of user/owner, computer, network device) Subject public key Version (Number) Hashing algorithm (data or signature)	1 1 1 1 1 1 1 max 3 3
2(c)(ii)	CA uses hashing algorithm .. To generate a message digest from the particular certificate Message digest is encrypted with CA's private key	1 1 1 3
2(c)(iii)	Need to know that the certificate is genuine (and has not been altered) // Authenticate or verify it (came from the CA)	1

Question	Answer	Marks																																													
3(a)	$S = (\bar{P} + (\overline{Q+R})) \cdot R$ \bar{P} $(\overline{Q+R})$ $(\bar{P} + (\overline{Q+R}))$ $\cdot R \quad (\text{must be outside final brackets})$ <p>Or</p> \bar{P} $(\overline{Q+R})$ $\bar{P} + (\overline{Q+R})$ $(\dots\dots\dots) \cdot R$	<p>4</p> <p>1</p> <p>1</p> <p>1</p> <p>1</p> <p>1</p> <p>1</p> <p>1</p> <p>1</p>																																													
3(b)	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>P</th> <th>Q</th> <th>R</th> <th>Working space</th> <th>S</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td></td><td>0</td></tr> <tr><td>0</td><td>0</td><td>1</td><td></td><td>1</td></tr> <tr><td>0</td><td>1</td><td>0</td><td></td><td>0</td></tr> <tr><td>0</td><td>1</td><td>1</td><td></td><td>1</td></tr> <tr><td>1</td><td>0</td><td>0</td><td></td><td>0</td></tr> <tr><td>1</td><td>0</td><td>1</td><td></td><td>0</td></tr> <tr><td>1</td><td>1</td><td>0</td><td></td><td>0</td></tr> <tr><td>1</td><td>1</td><td>1</td><td></td><td>0</td></tr> </tbody> </table> <p>2 marks all correct, 1 mark seven correct, 0 marks six or fewer correct</p>	P	Q	R	Working space	S	0	0	0		0	0	0	1		1	0	1	0		0	0	1	1		1	1	0	0		0	1	0	1		0	1	1	0		0	1	1	1		0	<p>2</p>
P	Q	R	Working space	S																																											
0	0	0		0																																											
0	0	1		1																																											
0	1	0		0																																											
0	1	1		1																																											
1	0	0		0																																											
1	0	1		0																																											
1	1	0		0																																											
1	1	1		0																																											
3(c)(i)	<p style="text-align: center;">PQ</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>00</td> <td>01</td> <td>11</td> <td>10</td> </tr> <tr> <td>R</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>1</td> <td>0</td> </tr> </table>		00	01	11	10	R	0	0	0	0		1	1	1	0	<p>1</p>																														
	00	01	11	10																																											
R	0	0	0	0																																											
	1	1	1	0																																											
3(c)(ii)	<p style="text-align: center;">PQ</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>00</td> <td>01</td> <td>11</td> <td>10</td> </tr> <tr> <td>R</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>0</td> <td>0</td> </tr> </table>		00	01	11	10	R	0	0	0	0		1	1	0	0	<p>1</p>																														
	00	01	11	10																																											
R	0	0	0	0																																											
	1	1	0	0																																											
3(c)(iii)	$S = \bar{P} \cdot R$	<p>1</p>																																													

Question	Answer	Marks
3(d)	$S = (\bar{P} + (\overline{Q+R})) \cdot R$ $S = (\bar{P} + (\overline{Q \cdot R})) \cdot R // \bar{P} \cdot R + (\overline{Q+R}) \cdot R$ $S = (\bar{P} \cdot R) + (\overline{Q \cdot R} \cdot R)$ $S = \bar{P} \cdot R + \overline{Q} \cdot 0$ $S = \bar{P} \cdot R + 0$ $S = \bar{P} \cdot R$	<p>3</p> <p>1</p> <p>1</p> <p>)</p> <p>) 1</p>

Question	Answer	Marks												
4(a)	<table border="0" style="width: 100%; text-align: center;"> <tr> <td style="width: 50%;">File organisation method</td> <td style="width: 10%;"></td> <td style="width: 40%;">File access method</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">random</td> <td style="border: none;">\</td> <td style="border: 1px solid black; padding: 5px;">sequential</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">serial</td> <td style="border: none;">/</td> <td style="border: 1px solid black; padding: 5px;">direct</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">sequential</td> <td style="border: none;">/</td> <td style="border: 1px solid black; padding: 5px;">direct</td> </tr> </table> <p>1 mark for random correct 1 mark for serial correct 2 marks for sequential correct (1 per correct line)</p>	File organisation method		File access method	random	\	sequential	serial	/	direct	sequential	/	direct	4
File organisation method		File access method												
random	\	sequential												
serial	/	direct												
sequential	/	direct												
4(b)(i)	File A: Serial Meter readings are submitted over time // added to the end of file Stored chronologically	<p>3</p> <p>1</p> <p>1</p> <p>1</p>												
4(b)(ii)	File B: Sequential Any two points from: Each customer has a unique account number Sorted on Account number High hit rate // Suitable for batch processing monthly statements	<p>3</p> <p>1</p> <p>1</p> <p>1</p> <p>1</p>												
4(b)(iii)	File C: Random Login without waiting // Random organisation allows fastest direct access to required record Low hit rate // Suitable for access to individual records	<p>3</p> <p>1</p> <p>1</p> <p>1</p>												

Question	Answer	Marks																		
5(a)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Option 1</th> <th style="width: 50%;">Option 2</th> <th></th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Application Layer</td> <td style="text-align: center;">Application Layer</td> <td></td> </tr> <tr> <td style="text-align: center;">Transport</td> <td style="text-align: center;">Transport (Layer)</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;">Internet</td> <td style="text-align: center;">Network (Layer)</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="text-align: center;">Network Interface</td> <td style="text-align: center;">(Data) Link (Layer)</td> <td style="text-align: center;">1</td> </tr> </tbody> </table>	Option 1	Option 2		Application Layer	Application Layer		Transport	Transport (Layer)	1	Internet	Network (Layer)	1	Network Interface	(Data) Link (Layer)	1	3			
Option 1	Option 2																			
Application Layer	Application Layer																			
Transport	Transport (Layer)	1																		
Internet	Network (Layer)	1																		
Network Interface	(Data) Link (Layer)	1																		
5(b)(i)	Peer-to-peer	1																		
5(b)(ii)	File sharing	1																		
5(b)(iii)	<p>Any four points from the following:</p> <ul style="list-style-type: none"> • Torrent descriptor file is made available • File to be shared is split into pieces • BitTorrent client software made available to other peers / users / computers Allowing them to work as seeds or leeches. <p>A peer can act as a 'seed' – used to upload pieces of a file Peer downloading file can get pieces from different seeds simultaneously</p> <ul style="list-style-type: none"> • Once a peer has a piece of the file it can become a seed for the parts downloaded Leeches download much more than they upload • Central server called a tracker keeps records of all the peers ('swarm') and the parts of the file they have Can pause and restart at any time. 	Max 4																		
5(c)	<table border="0" style="width: 100%;"> <tr> <td>Any two protocols from:</td> <td></td> </tr> <tr> <td>HTTP/HTTPS ...</td> <td style="text-align: right;">1</td> </tr> <tr> <td>Used for transfer of web pages from server to client</td> <td style="text-align: right;">1</td> </tr> <tr> <td>FTP ...</td> <td style="text-align: right;">1</td> </tr> <tr> <td>Used for interactive file transfer</td> <td style="text-align: right;">1</td> </tr> <tr> <td>SMTP ...</td> <td style="text-align: right;">1</td> </tr> <tr> <td>Used for sending email messages</td> <td style="text-align: right;">1</td> </tr> <tr> <td>POP3 ...</td> <td style="text-align: right;">1</td> </tr> <tr> <td>Used for incoming email messages</td> <td style="text-align: right;">1</td> </tr> </table>	Any two protocols from:		HTTP/HTTPS ...	1	Used for transfer of web pages from server to client	1	FTP ...	1	Used for interactive file transfer	1	SMTP ...	1	Used for sending email messages	1	POP3 ...	1	Used for incoming email messages	1	Max 4
Any two protocols from:																				
HTTP/HTTPS ...	1																			
Used for transfer of web pages from server to client	1																			
FTP ...	1																			
Used for interactive file transfer	1																			
SMTP ...	1																			
Used for sending email messages	1																			
POP3 ...	1																			
Used for incoming email messages	1																			

Question	Answer	Marks	
6(a)(i)	Monitoring system	1	
6(a)(ii)	There is no element of 'control' in the system // the system does not alter conditions in the building if sensors triggered	1	
6(a)(iii)	Any two sensors from: Sound / acoustic Pressure Infra-red / motion /proximity Temperature / Thermal Light Smoke Tilt	Max 2	
6(b)(i)	<pre> 01 ForEver ← FALSE //TRUE 02 REPEAT 03 FOR FloorCounter ← 1 TO NoOfFloors 04 FOR SensorCounter ← 1 TO NumberOfSensors 05 READ Sensor(SensorCounter) on Floor(FloorCounter) 06 IF Sensor value outside range 07 THEN 08 OUTPUT "Problem on Floor ", FloorCounter 09 ENDIF 10 ENDFOR 11 ENDFOR 12 // 13 // Delay loop 14 // Delay loop 15 // 16 UNTIL ForEver/Forever = TRUE // NOT ForEver / ForEver = FALSE </pre>	<p>1</p> <p>1</p> <p>1</p>	3
6(b)(ii)	FOR Counter ← 1 TO 999999 (any "large" number) ENDFOR	1	
6(b)(iii)	To allow time to elapse between readings	1	
6(c)(i)	To identify which <u>sensor</u> caused the interrupt	1	
6(c)(ii)	Display appropriate warning message On the correct monitor	1 1	2