Cambridge International AS & A Level

Cambridge International Examinations
Cambridge International Advanced Subsidiary and Advanced Level

PHYSICS **9702/41**

Paper 4 A Level Structured Questions **October/November 2016**

MARK SCHEME

Maximum Mark: 100

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2016 series for most Cambridge IGCSE®, Cambridge International A and AS Level components and some Cambridge O Level components.

1 (a) gravitational force provides/is the centripetal force — B1

$GMm/r^2 = mv^2/r$ *or* $GMm/r^2 = mr\omega^2$
and $v = 2\pi r/T$ *or* $\omega = 2\pi/T$ — M1

with algebra to $T^2 = 4\pi^2 r^3/GM$ — A1 [3]

or

acceleration due to gravity is the centripetal acceleration — (B1)

$GM/r^2 = v^2/r$ *or* $GM/r^2 = r\omega^2$
and $v = 2\pi r/T$ *or* $\omega = 2\pi/T$ — (M1)

with algebra to $T^2 = 4\pi^2 r^3/GM$ — (A1)

(b) (i) equatorial orbit/orbits (directly) above the equator — B1

from west to east — B1 [2]

(ii) $(24 \times 3600)^2 = 4\pi^2 r^3/(6.67 \times 10^{-11} \times 6.0 \times 10^{24})$ — C1

$r^3 = 7.57 \times 10^{22}$

$r = 4.2 \times 10^7$ m — A1 [2]

(c) $(T/24)^2 = \{(2.64 \times 10^7)/(4.23 \times 10^7)\}^3$
$= 0.243$ — B1

$T = 12$ hours — A1 [2]

or

$k\ (= T^2/r^3) = 24^2/(4.23 \times 10^7)^3$
$= 7.61 \times 10^{-21}$ — (B1)

$T^2\ (= kr^3) = 7.61 \times 10^{-21} \times (2.64 \times 10^7)^3$
$= 140$

$T = 12$ hours — (A1)

2 (a) (i) $p \propto T$ *or* $pV/T =$ constant *or* $pV = nRT$ — C1

$T\ (= 5 \times 300 =)$ 1500 K — A1 [2]

(ii) $pV = nRT$

$1.0 \times 10^5 \times 4.0 \times 10^{-4} = n \times 8.31 \times 300$
or
$5.0 \times 10^5 \times 4.0 \times 10^{-4} = n \times 8.31 \times 1500$ — C1

$n = 0.016$ mol — A1 [2]

(b)	**(i)**	**1.**	heating/thermal energy supplied	B1	
		2.	work done on/to system	B1	[2]
	(ii)	**1.**	240 J	A1	
		2.	same value as given in **1.** (= 240 J) **and** zero given for **3.**	A1	
		3.	zero	A1	[3]

3 **(a)** $2k/m = \omega^2$ M1

$\omega = 2\pi f$ M1

$(2 \times 64 / 0.810) = (2\pi \times f)^2$ leading to $f = 2.0$ Hz A1 [3]

(b) $v_0 = \omega x_0$ *or* $v_0 = 2\pi f x_0$
or
$v = \omega(x_0^2 - x^2)^{1/2}$ and $x = 0$ C1

$v_0 = 2\pi \times 2.0 \times 1.6 \times 10^{-2}$

$= 0.20\,\text{m s}^{-1}$ A1 [2]

(c) frequency: reduced/decreased B1
maximum speed: reduced/decreased B1 [2]

4 **(a)** **(i)** noise/distortion is removed (from the signal) B1
the (original) signal is reformed/reproduced/recovered/restored B1 [2]

or

signal detected above/below a threshold creates new signal (B1)
of 1s and 0s (B1)

(ii) noise is superposed on the (displacement of the) signal/cannot be distinguished
or
analogue/signal is continuous (so cannot be regenerated)
or
analogue/signal is not discrete (so cannot be regenerated) B1

noise is amplified with the signal B1 [2]

(b) (i) gain/dB = $10 \lg (P_2 / P_1)$

$32 = 10 \lg [P_{MIN} / (0.38 \times 10^{-6})]$
or
$-32 = 10 \lg (0.38 \times 10^{-6} / P_{MIN})$ C1

$P_{MIN} = 6.0 \times 10^{-4}$ W A1 [2]

(ii) attenuation $= 10 \lg [(9.5 \times 10^{-3}) / (6.02 \times 10^{-4})]$ C1

$= 12$ dB

attenuation per unit length (= 12/58) = 0.21 dB km^{-1} A1 [2]

5 (a) in an electric field, charges (in a conductor) would move B1

no movement of charge so zero field strength
or
charge moves until $F = 0$ / $E = 0$ B1 [2]

or

charges in metal do not move (B1)
no (resultant) force on charges so no (electric) field (B1)

(b) at P, $E_A = (3.0 \times 10^{-12}) / [4\pi\varepsilon_0 (5.0 \times 10^{-2})^2]$ (= 10.79 N C^{-1}) M1

at P, $E_B = (12 \times 10^{-12}) / [4\pi\varepsilon_0 (10 \times 10^{-2})^2]$ (= 10.79 N C^{-1}) M1

or

$(3.0 \times 10^{-12}) / [4\pi\varepsilon_0 (5.0 \times 10^{-2})^2] - (12 \times 10^{-12}) / [4\pi\varepsilon_0 (10 \times 10^{-2})^2] = 0$
or
$(3.0 \times 10^{-12}) / [4\pi\varepsilon_0 (5.0 \times 10^{-2})^2] = (12 \times 10^{-12}) / [4\pi\varepsilon_0 (10 \times 10^{-2})^2]$ (M2)

fields due to charged spheres are (equal and) opposite in direction, so $E = 0$ A1 [3]

(c) potential $= 8.99 \times 10^9 \{(3.0 \times 10^{-12}) / (5.0 \times 10^{-2}) + (12 \times 10^{-12}) / (10 \times 10^{-2})\}$ C1

$= 1.62$ V A1 [2]

(d) $\frac{1}{2} m v^2 = qV$

$E_K = \frac{1}{2} \times 107 \times 1.66 \times 10^{-27} \times v^2$ C1

$qV = 47 \times 1.60 \times 10^{-19} \times 1.62$ C1

$v^2 = 1.37 \times 10^8$

$v = 1.2 \times 10^4$ m s^{-1} A1 [3]

6	**(a)**	reference to input (voltage) and output (voltage) there is no time delay between change in input and change in output	B1 B1	[2]
		or		
		reference to rate at which output voltage changes infinite rate of change (of output voltage)	(B1) (B1)	
	(b) **(i)**	$2.00 / 3.00 = 1.50 / R$	C1	
		or		
		$V_+ = (3.00 \times 4.5) / (2.00 + 3.00) = 2.7$ $2.7 = 4.5 \times R / (R + 1.50)$	(C1)	
		resistance = 2.25 kΩ	A1	[2]
	(ii) **1.**	correct symbol for LED two LEDs connected with opposite polarities between V_{OUT} and earth	M1 A1	[2]
	2.	below 24 °C, $R_T > 1.5$ kΩ or resistance of thermistor increases/high	B1	
		$V_- < V_+$ or V_- decreases/low (must not contradict initial statement)	M1	
		V_{OUT} is positive/+5 (V) and LED labelled as 'pointing' from V_{OUT} to earth	A1	[3]
7	**(a)**	region (of space) where a force is experienced by a particle	B1	[1]
	(b) **(i)**	gravitational	B1	
	(ii)	gravitational and electric	B1	
	(iii)	gravitational, electric and magnetic	B1	[3]
	(c) **(i)**	force (always) normal to direction of motion	M1	
		(magnitude of) force constant *or* speed is constant/kinetic energy is constant	M1	
		magnetic force provides/is the centripetal force	A1	[3]
	(ii)	$mv^2 / r = Bqv$	B1	
		momentum or p or $mv = Bqr$	B1	[2]

8 strong uniform magnetic field B1

nuclei precess/rotate about field (direction) (1)

radio-frequency pulse (applied) B1

R.F. or pulse is at Larmor frequency/frequency of precession (1)

causes resonance/excitation (of nuclei)/nuclei absorb energy B1

on relaxation/de-excitation, nuclei emit r.f./pulse B1

(emitted) r.f./pulse detected and processed (1)

non-uniform magnetic field B1

allows position of nuclei to be located B1

allows for location of detection to be changed/different slices to be studied (1)

any two of the points marked (1) B2 [8]

9 **(a)** (induced) e.m.f. proportional to rate of change of (magnetic) flux (linkage) M1 A1 [2]

(b) flux linkage $= BAN$

$= \pi \times 10^{-3} \times 2.8 \times \pi \times (1.6 \times 10^{-2})^2 \times 85 = 6.0 \times 10^{-4}$ Wb B1 [1]

(c) e.m.f. $= \Delta N\Phi / \Delta t$

$= (6.0 \times 10^{-4} \times 2) / 0.30$ C1

$= 4.0\,\text{mV}$ A1 [2]

(d) sketch: $E = 0$ for $t = 0 \rightarrow 0.3\,\text{s}$, $0.6\,\text{s} \rightarrow 1.0\,\text{s}$, $1.6\,\text{s} \rightarrow 2.0\,\text{s}$ B1

$E = 4$ mV for $t = 0.3\,\text{s} \rightarrow 0.6\,\text{s}$ (either polarity) B1

$E = 2$ mV for $t = 1.0\,\text{s} \rightarrow 1.6\,\text{s}$ B1

with opposite polarity B1 [4]

10 (a) electromagnetic radiation/photons incident on a surface — B1

causes emission of electrons (from the surface) — B1 [2]

(b) $E = hc / \lambda$

$= (6.63 \times 10^{-34} \times 3.00 \times 10^{8}) / (436 \times 10^{-9})$ — C1

$= 4.56 \times 10^{-19}$ J $(4.6 \times 10^{-19}$ J) — A1 [2]

(c) (i) $\Phi = hc / \lambda_0$

$\lambda_0 = (6.63 \times 10^{-34} \times 3.00 \times 10^{8}) / (1.4 \times 1.60 \times 10^{-19})$ — C1

$= 890$ nm — A1 [2]

(ii) $\lambda_0 = (6.63 \times 10^{-34} \times 3.00 \times 10^{8}) / (4.5 \times 1.60 \times 10^{-19})$

$= 280$ nm — A1 [1]

(d) caesium:
wavelength of photon less than threshold wavelength (or v.v.)
or
$\lambda_0 = 890$ nm > 436 nm
so yes — A1

tungsten:
wavelength of photon greater than threshold wavelength (or v.v.)
or
$\lambda_0 = 280$ nm < 436 nm
so no — A1 [2]

11 in metal, conduction band overlaps valence band/no forbidden band/no band gap — B1

as temperature rises, no increase in number of free electrons/charge carriers — B1

as temperature rises, lattice vibrations increase — M1

(lattice) vibrations restrict movement of electrons/charge carriers — M1

(current decreases) so resistance increases — A1 [5]

12 (a) (i) time for number of atoms/nuclei or activity to be reduced to one half — M1

reference to (number of…) original nuclide/single isotope
or
reference to half of original value/initial activity — A1 [2]

(ii) $A = A_0 \exp(-\lambda t)$ and either $t = t_{½}$, $A = ½A_0$ or $½A_0 = A_0 \exp(-\lambda t_{½})$ — M1

so $\ln 2 = \lambda t_{½}$ (and $\ln 2 = 0.693$), hence $0.693 = \lambda t_{½}$ — A1 [2]

(b) $A = \lambda N$

$N = 200 / (2.1 \times 10^{-6})$ — C1

$= 9.52 \times 10^{7}$ — C1

mass $= (9.52 \times 10^{7} \times 222 \times 10^{-3}) / (6.02 \times 10^{23})$
or
mass $= 9.52 \times 10^{7} \times 222 \times 1.66 \times 10^{-27}$ — C1

$= 3.5 \times 10^{-17}$ kg — A1 [4]